

171

PHYSICAL STATE: Liquid
EVAPORATION RATE (vs Butyl Acetate): Faster
Heavier
% VOLATILE BY WEIGHT: 78.50
Insoluble

ODOR: Alcoholic
VAPOR DENSITY (vs air):
SOLUBILITY IN WATER:

SECTION D – FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 73° F Tagliabue Closed Tester (ASTM D 56-79)
FLAMMABLE LIMITS: Lower: 3.3% Upper: 19.00%
EXTINGUISHING MEDIA: Alcohol Foam, CO₂, Dry Chemical, Water Fog
SPECIAL FIREFIGHTING PROCEDURES: Class I-B Flammable Liquid. Vapors from this product may concentrate in confined spaces and form an explosive mixture.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Product may produce hazardous fumes or hazardous decomposition products. Heated containers may rupture violently from excessive heat.

SECTION E – HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: Mixture. See section B, hazardous components of mixture.
PRIMARY ROUTES OF ENTRY: Skin contact. Inhalation
EFFECTS OF ACUTE OVEREXPOSURE: Prolonged or repeated exposure to this product may dry skin and cause dermatitis. Prolonged or repeated exposure may cause kidney, liver, lungs and heart damage.

SECTION F – EMERGENCY FIRST AID PROCEDURES

EYES: Flush immediately with plenty of water for at least 15 minutes. Remove contact lenses if worn. Get medical attention if irritation persists.

SKIN: Thoroughly wash exposed area with soap and water. Remove contaminated clothing.

INGESTION: If swallowed, get medical attention immediately. Induce vomiting immediately, as directed by medical personnel.

INHALATION: Remove individual to fresh air

SECTION G – REACTIVITY DATA

HAZARDOUS POLYMERIZATION: Will not occur

STABILITY: Stable

INCOMPATIBILITY: Oxidizers and alkali metal hydroxides

CONDITIONS TO AVOID: Hot storage (above 80° F), sparks and open flames. Avoid contact with strong oxidizing agents.

SECTION H – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK:

SMALL SPILL: Remove all ignition sources. Small spills may be collected with absorbent materials. Wash area with soap and water, collect rinsates and containerize for disposal.

LARGE SPILL: Remove all ignition sources. Vapors are heavier than air and will concentrate at ground level. Contain spill immediately. Prevent from getting into public sewer, water systems or surface waters. Place in suitable container for disposal

WASTE DISPOSAL INFORMATION: Dispose in accordance with Local, State and Federal regulations.

SECTION I – PROTECTIVE EQUIPMENT TO BE USED

VENTILATION: Provide sufficient mechanical ventilation

PROTECTIVE GLOVES: If prolonged or repeated contact, wear impervious gloves

EYE PROTECTION; Chemical splash goggles in compliance with OSHA regulations are advised

RESPIRATORY PROTECTION: Not necessary under normal use conditions

OTHER PROTECTIVE EQUIPMENT: Emergency eye wash stations should be readily available. Apron

SECTION J – STORAGE AND HANDLING

Keep in cool, dry, ventilated storage and in closed containers away from all sources of ignition. Wash thoroughly after handling. Avoid contact with eyes. Avoid breathing vapors, mist or aerosols. Use only with adequate ventilation.

SECTION K – SPECIAL PRECAUTIONS

WARNING: Hot Organic chemical vapors or mists are susceptible to sudden spontaneous combustion when mixed with air. Ignition may occur at temperatures below those published in the literature as autoignition or ignition temperatures.

MSDS- INDELIBLE INK(ss)

DATE \@ "MM/dd/yy" 02/02/10

PAGE

PAGE 1